

Ny state 6 cylinder championship

RULES

1. ALL DRIVERS MUST BE AT LEAST 16, {16 and 17 must have a signed parents release form} DRIVER MUST WEAR FULL FACE HELMET AND EYE PROTECTION
2. ANY 4 CYLINDER OR 6 CYLINDER FRONT WHEEL DRIVE PERMITTED NO ALL WHEEL DRIVES, TRUCKS OR VANS. car must be oem with 4/6 cylinder
3. ALL GLASS, AIR BAGS, MOLDINGS AND WHEEL WEIGHTS MUST BE REMOVED
4. Battery may be relocated inside car on passenger side floorboard secured to the floor AND COVERED WITH A RUBBER MAT.. ONLY 1 12 VOLT BATTERY ALLOWED
5. GAS TANKS MAY BE RELOCATED INSIDE CAR AS LONG AS THEY ARE SECURED TO THE FLOOR AND COVERED..A METAL MARINE TANK MUST BE USED IF TANK IS MOVED..NO MORE THAN 3 GALLONS OF GAS ALLOWED IN ANY TANK. IF TANK IS LOCATED IN FRONT OF THE REAR AXLE IT MAY BE LEFT IN STOCK POSITION
6. TRUNK AND DOORS MAY BE WELDED 2 INCHES FOR EVERY 10 INCHES OF SEAMS
7. ROLL CAGE, HALO BAR OR SEAT BRACE MAY BE USED BUT NOT FURTHER BACK THAN 6 INCHES BEHIND DRIVERS SEAT
8. MAXIMUM TIRE SIZE 16" 6 PLY STREET LEGAL DOT. ALLOWED..NO STUDDERED TIRES NO INNER TIRES OR FILLING OF TIRES, TUBES ALLOWED
9. WATER ONLY IN RADIATORS.
10. HOODS MAY BE BOLTED DOWN in 4 SPOTS USING 5/8 INCH BOLTS NO LONGER THAN 6 INCHES.

11. CARS MUST HAVE GOOD WORKING BREAKS; THIS WILL BE CHECKED AND ENFORCED.

12. NO FROZEN STRUTS OR SHOCKS CAR MUST BOUNCE FREELY

13. FRONT BUMPERS MAY BE EXCHANGED... ANY OEM CAR BUMPER ALLOWED, MUST BE CUT TO WIDTH OF CAR..BUMPER MAY BE WELDED TO FRAME OR BUMPER SHOCKS..YOU MAY ADD 1 PIECE OF FLAT STOCK TO EACH SIDE TO WELD THE BUMPER ON... FLAT STOCK WILL BE ¼ INCH THICK.. 3 INCH BY 6 INCH MAXIMUM... ONLY WELDING ON THE BUMPER ALLOWED IS ON THE BACK OF IT TO ATTACH IT TO CAR. DO NOT WELD SEAMS, PAINT OR COVER FRAME HOLES OF CAR.

14. THE ONLY WELDING ON THE CAR IS IN THE RULES ABOVE, NO WELDING OF FRAME NO PATCHING NO WELDING OF INTERIOR SEAMS

15. IF IT'S NOT IN THE RULES ABOVE DON'T DO IT

16. PRE DENTING IS ALLOWED

17.ANY QUESTIONS PLEASE CALL BRIAN 585-259-7273